

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A01N 1/02	A2	(11) International Publication Number: WO 00/18226 (43) International Publication Date: 6 April 2000 (06.04.00)
<p>(21) International Application Number: PCT/US99/22582</p> <p>(22) International Filing Date: 29 September 1999 (29.09.99)</p> <p>(30) Priority Data: 09/162,128 29 September 1998 (29.09.98) US</p> <p>(71) Applicant: LIFE SCIENCE HOLDINGS, INC. [US/US]; 1510 West Montana Street, Chicago, IL 60614-2013 (US).</p> <p>(72) Inventors: OWEN, Donald, R.; Vital Assist, Inc., Suite I, 5701 Crawford Street, Harahan, LA 70123 (US). KRAVITZ, David, C.; Life Science Holdings, Inc., Suite 500, 1510 West Montana Street, Chicago, IL 60614-2013 (US).</p> <p>(74) Agents: OLIFF, James, A. et al.; Oliff & Berridge, plc, P.O. Box 19928, Alexandria, VA 22320 (US).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>Without international search report and to be republished upon receipt of that report.</i></p>
<p>(54) Title: APPARATUS AND METHOD FOR MAINTAINING AND/OR RESTORING VIABILITY OF ORGANS</p>		
<p>(57) Abstract</p> <p>An organ perfusion apparatus and method for monitoring, sustaining and/or restoring the viability of the organ and for preserving the organ for storage and/or transport perfuse the organ at normothermic temperatures (normothermic perfusion mode), preferably prior to and followed by organ perfusion at hypothermic temperatures (hypothermic perfusion mode) for transport and/or storage of the organ. The restoring of organ viability is accomplished by restoring high energy nucleotide (e.g., ATP) levels in the organ, which were reduced by warm ischemia time, by perfusing the organ with a medical fluid, such as an oxygenated cross-linked hemoglobin-based bicarbonate medical fluid, at normothermic temperatures. In the normothermic perfusion mode, organ perfusion pressure is preferably controlled in response to a sensor disposed in an end of tubing placed in the organ, by a pneumatically pressurized medical fluid reservoir which may be used in combination with a stepping motor/cam valve which provides for perfusion pressure fine tuning, preventing overpressurization and providing emergency flow cut-off. In the hypothermic mode, the organ is perfused with a medical fluid, preferably a simple crystalloid solution augmented with antioxidants, intermittently or at a slow continuous flow rate. The medical fluid may be fed into the organ by gravity from an intermediary tank which has a low pressure head so overpressurization of the organ is avoided. In either mode, preventing overpressurization prevents and/or reduces damage to the vascular endothelial lining and to the organ tissue in general. Also, viability of the organ may be automatically monitored in either mode, preferably by monitoring fluid characteristics of the medical fluid that has been perfused through the organ, such fluid characteristics being indicative of organ viability. The perfusion process can be automatically controlled using a control program.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

APPARATUS AND METHOD FOR MAINTAINING AND/OR RESTORING VIABILITY OF ORGANS

BACKGROUND OF THE INVENTION

1. Field of Invention

5 The invention relates to an apparatus and method for perfusing one or more organs to monitor, sustain and/or restore the viability of the organ(s) and/or for transporting and/or storing the organ(s).

2. Description of Related Art

10 Preservation of organs by machine perfusion has been accomplished at hypothermic temperatures with or without computer control with crystalloid perfusates and without oxygenation. See, for example, U.S. Patent Nos. 5,149,321, 5,395,314, 5,584,804, 5,709,654 and 5,752,929 and U.S. Patent Application No. 08/484,601 to Klatz et al., which are hereby incorporated by reference. Hypothermic temperatures provide a decrease in organ metabolism, lower the energy
15 requirements, delay the depletion of high energy phosphate reserves and accumulation of lactic acid and retard the morphological and functional deterioration associated with disruption of blood supply. Oxygen can not be utilized efficiently by mitochondria below approximately 20°C to produce energy and the reduction in
20 low temperatures allows high free radical formation. The removal of oxygen from perfusates during low temperature machine perfusion has even proven helpful in improving organ transplant results by some investigators.

Reduction in potential oxygen damage is also accomplished via the addition of antioxidants to the perfusate. In particular, this has proven useful in reducing organ
25 damage after long warm ischemia times. Numerous other perfusate additives have also been reported to improve the outcome of machine perfusion.

Ideally organs would be procured in a manner which limits their warm ischemia time to essentially zero. Unfortunately, in reality, many organs, especially from non-beating heart donors, are procured after extended warm ischemia time
30 periods (i.e. 45 minutes or more). The machine perfusion of these organs at low temperature has demonstrated significant improvement (Transpl Int 1996 Daemen). Further, prior art teaches that the low temperature machine perfusion of organs is

preferred at low pressures (Transpl. Int 1996 Yland) with roller or diaphragm pumps delivering the perfusate at a controlled pressure. Numerous control circuits and pumping configurations have been utilized to achieve this objective and to machine perfuse organs in general. See, for example, U.S. Patents Nos. 5,338,662 and
5 5,494,822 to Sadri; U.S. Patent No. 4,745,759 to Bauer et al.; U.S. Patents Nos. 5,217,860 and 5,472,876 to Fahy et al.; U.S. Patent No. 5,051,352 to Martindale et al.; U.S. Patent No. 3,995,444 to Clark et al.; U.S. Patent No. 4,629,686 to Gruenberg; U.S. Patents Nos. 3,738, 914 and 3,892,628 to Thorne et al.; U.S. Patents Nos. 5,285,657 and 5,476,763 to Bacchi et al.; U.S. Patent No. 5,157,930 to McGhee
10 et al.; and U.S. Patent No. 5,141,847 to Sugimachi et al. However, the use of such pumps for machine perfusion of organs increases the risk of overpressurization of the organ should the organ perfusion apparatus malfunction. High pressure perfusion (e.g., above about 60 mm Hg) can wash off the vascular endothelial lining of the organ and in general damages organ tissue, in particular at hypothermic temperatures
15 where the organ does not have the neurological or endocrinal connections to protect itself by dilating its vasculature under high pressure.

Furthermore, the techniques used for assessment of the viability of these machine perfused organs have been a critical factor in limiting the organs from greater use. While increased organ resistance (i.e., pressure/flow) measurements during
20 machine perfusion are a useful indicator, they demonstrate only the worst case situations.

During the low temperature machine perfusion of organs which have been damaged by warm ischemia time or by the machine perfusion itself, the organs will elute intracellular and endothelial as well as membrane constituents. Over the years
25 the appearance of various ubiquitous intracellular enzymes, such as lactic dehydrogenase (LDH) and alkaline phosphatase, in the perfusate has been used as a biomarker of organ damage. Recently, the determination of the presence of alpha glutathione-S-transferase (a-GST) and Pi glutathione-S-transferase (p-GST) in low temperature machine perfusion perfusates has proven a satisfactory indicator in
30 predicting the functional outcome of non-beating heart donor kidney grafts before transplantation (Transpl 1997 Daemen).

The prior art has also addressed the need to restore or maintain an organ's physiological function after preservation for an extended period of time at

hypothermic temperatures. In particular, U.S. Patent No. 5,066,578 to Wikman-Coffelt discloses an organ preservation solution that contains large amounts of pyruvate. Wikman-Coffelt teaches that flooding of the organ with pyruvate bypasses glycolysis, the step in the cell energy cycle that utilizes adenosine triphosphate (ATP) to produce pyruvate, and pyruvate is then available to the mitochondria for oxidative phosphorylation producing ATP. Wikman-Coffelt teaches perfusing or washing an organ at a warm temperature with a first preservation solution containing pyruvate for removal of blood or other debris from the organ's vessels and to vasodilate, increase flow and load the cells with an energy supply in the form of a clean substrate, namely the pyruvate. Wikman-Coffelt teaches that the pyruvate prevents edema, ischemia, calcium overload and acidosis as well as helps preserve the action potential across the cell membrane. The organ is then perfused with a second perfusion solution containing pyruvate and a small percentage of ethanol in order to stop the organ from working, vasodilate the blood vessels allowing for full vascular flow, continue to load the cells with pyruvate and preserve the energy state of the organ. Finally the organ is stored in a large volume of the first solution for 24 hours or longer at temperatures between 4°C and 10°C.

However, the mitochondria are the source of energy in cells and need significant amounts of oxygen to function. Organs naturally have significant pyruvate levels, and providing an organ with additional pyruvate will not assist in restoring and/or maintaining an organ's full physiological function if the mitochondria are not provided with sufficient oxygen to function. Further, briefly flooding an organ with pyruvate may, in fact, facilitate tearing off of the vascular endothelial lining of the organ.

U.S. Patent No. 5,599,659 to Brasile et al. also discloses a preservation solution for warm preservation of tissues, explants, organs and endothelial cells. Brasile et al. teach disadvantages of cold organ storage, and proposed warm preservation technology as an alternative. Brasile et al. teach that the solution has an enhanced ability to serve as a medium for the culture of vascular endothelium of tissue, and as a solution for organs for transplantation using a warm preservation technology because it is supplemented with serum albumin as a source of protein and colloid; trace elements to potentiate viability and cellular function; pyruvate and adenosine for oxidative phosphorylation support; transferrin as an attachment factor;

insulin and sugars for metabolic support and glutathione to scavenge toxic free radicals as well as a source of impermeant; cyclodextrin as a source of impermeant, scavenger, and potentiator of cell attachment and growth factors; a high Mg^{++} concentration for microvessel metabolism support; mucopolysaccharides, comprising primarily chondroitin sulfates and heparin sulfates, for growth factor potentiation and hemostasis; and ENDO GRO™ as a source of colloid, impermeant and specific vascular growth promoters. Brasile et al. further teach warm perfusing an organ for up to 12 hours at 30°C, or merely storing the organ at temperatures of 25°C in the preservation solution.

However, flooding an organ with such chemicals is insufficient to arrest or repair ischemic injury where the mitochondria are not provided with sufficient oxygen to function to produce energy. The oxygen needs of an organ at more than 20°C are substantial and cannot be met by a simple crystalloid at reasonable flows. Further, assessment of the viability of an organ is necessary before the use of any type of solution can be determined to have been fruitful.

SUMMARY OF THE INVENTION

The present invention focuses on avoiding damage to the organ during perfusion while monitoring, sustaining and/or restoring the viability of the organ and preserving the organ for storage and/or transport. The invention is directed to an apparatus and method for perfusing an organ to monitor, sustain and/or restore the viability of the organ and/or for transporting and/or storing the organ. More particularly, the organ perfusion apparatus and method according to the invention monitor, sustain and/or restore organ viability by perfusing the organ at normothermic temperatures (normothermic perfusion mode) preferably prior to and followed by organ perfusion at hypothermic temperatures (hypothermic perfusion mode) for transport and/or storage of the organ.

The restoring of organ viability may be accomplished by restoring high energy nucleotide (e.g., adenosine triphosphate (ATP)) levels and enzyme levels in the organ which were reduced by warm ischemia time by perfusing the organ with an oxygenated medical fluid, such as an oxygenated cross-linked hemoglobin-based bicarbonate medical fluid, at normothermic or near-normothermic temperatures. The organ may be flushed with a medical fluid prior to perfusion with the oxygenated medical fluid. Such perfusion can be performed at either normothermic or

hypothermic temperatures. The medical fluid preferably contains little or no oxygen and preferably includes antioxidants, both molecular (e.g., 2-ascorbic acid tocopherol) and enzymatic (e.g., catalase and superoxide dismutase (SOD)). Normothermic perfusion can be performed in vivo as well as in vitro. Such perfusion arrests or repairs ischemic injury in preparation of transport, storage and/or transplant of the organ.

In the normothermic perfusion mode, gross organ perfusion pressure is preferably provided by a pneumatically pressurized medical fluid reservoir controlled in response to a sensor disposed in an end of tubing placed in the organ, which may be used in combination with a stepping motor/cam valve or pinch valve which provides for perfusion pressure fine tuning, prevents overpressurization and/or provides emergency flow cut-off. Substantially eliminating overpressurization prevents and/or reduces damage to the vascular endothelial lining and to the organ tissue in general. Viability of the organ may be monitored, preferably automatically, in the normothermic perfusion mode, preferably by monitoring organ resistance (pressure/flow) and/or pH, pO_2 , pCO_2 , LDH, T/GST and Tprotein levels in the medical fluid that has been perfused through the organ and collected.

Normothermic perfusion may be followed by hypothermic perfusion. In the hypothermic mode, the organ is perfused with a medical fluid containing substantially no oxygen, preferably a simple crystalloid solution preferably augmented with antioxidants, intermittently or at a slow continuous flow rate. Hypothermic perfusion also can be performed in vivo as well as in vitro. Hypothermic perfusion reduces the organ's metabolic rate allowing the organ to be preserved for extended periods of time. The medical fluid is preferably fed into the organ by gravity from an intermediary tank which has a low pressure head so overpressurization of the organ is avoided. Substantially eliminating overpressurization prevents or reduces damage to the vascular endothelial lining of the organ and to the organ tissue in general, in particular at hypothermic temperatures when the organ has less ability to protect itself by vascular constriction. Viability of the organ may also be monitored, preferably automatically, during the recovery process, preferably by monitoring organ resistance (pressure/flow) and/or pH, pO_2 , pCO_2 , LDH, T/GST and Tprotein levels in the medical fluid that has been perfused through the organ and collected.

This invention includes a control system for automatically controlling perfusion of one or more organs by selecting between perfusion modes and control parameters. Automatic perfusion may be based on sensed conditions in the system or manually input parameters. The system may be preprogrammed or programmed during use. Default values and viability checks are utilized.

The present invention also provided an organ cassette which allows an organ to be easily and safely moved between apparatus for perfusing, storing and/or transporting the organ.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other aspects and advantages of the invention will become apparent from the following detailed description of embodiments when taken in conjunction with the accompanying drawings, in which:

Fig. 1 is an organ perfusion apparatus according to the invention;

Fig. 2 is a schematic diagram of the apparatus of Fig. 1;

Fig. 3 is a diagram of the electronics of the apparatus of Fig. 1;

Fig. 4 is an exploded view of a first pump module of a combined pump, filtration, oxygenation and/or debubbler apparatus according to the invention;

Fig. 5 is an exploded view of a filtration module of a combined pump, filtration, oxygenation and/or debubbler apparatus according to the invention;

Fig. 6 is an exploded view of an oxygenation module of a combined pump, filtration, oxygenation and/or debubbler apparatus according to the invention;

Fig. 7 is an exploded view of a debubbler module of a combined pump, filtration, oxygenation and/or debubbler apparatus according to the invention;

Fig. 8 is an exploded view of a second pump module of a combined pump, filtration, oxygenation and/or debubbler apparatus according to the invention;

Fig. 9 is an exploded perspective view showing the modules of Figs. 4-8 assembled together;

Fig. 10 is a front perspective view of an assembled modular combined pump, filtration, oxygenation and/or debubbler apparatus according to the invention;

Figs. 11A - 11D show side perspective views of various embodiments of an organ cassette according to the invention;

Fig. 12 is an organ perfusion apparatus configured to simultaneously perfuse multiple organs;

Figs. 13A and 13B show a stepping motor/cam valve according to the invention;

Figs. 14A - 14F show another stepping motor/cam valve according to the invention; and

5 Fig. 15 shows a block diagram that schematically illustrates the control system according to the invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

For a general understanding of the features of the invention, reference is made to the drawings. In the drawings, like reference numerals have been used throughout to designate like elements.

10 Figure 1 shows an organ perfusion apparatus 1 according to the invention. Figure 2 is a schematic illustration of the apparatus of Fig. 1. The apparatus 1 is preferably at least partially microprocessor controlled, and pneumatically actuated. The microprocessor 150 connection to the sensors, valves, thermoelectric units and pumps of the apparatus 1 is schematically shown in Fig. 3.

15 The organ perfusion apparatus 1 is capable of perfusing one or more organs simultaneously, at both normothermic and hypothermic temperatures (hereinafter, normothermic and hypothermic perfusion modes). All medical fluid contact surfaces are preferably formed of or coated with materials compatible with the medical fluid used, more preferably non-thrombogenic materials. As shown in Fig. 1, the apparatus 20 1 includes a housing 2 which includes front cover 4, which is preferably translucent, and a reservoir access door 3. The apparatus preferably has one or more control and display areas 5a, 5b, 5c, 5d for monitoring and controlling perfusion.

As schematically shown in Fig. 2, enclosed within the housing 2 is a reservoir 25 10 which preferably includes three reservoir tanks 15a, 15b, 17. Two of the reservoir tanks 15a, 15b are preferably standard one liter infusion bags, each with a respective pressure cuff 16a, 16b. A pressure source 20 can be provided for pressurizing the pressure cuffs 16a, 16b. The pressure source 20 is preferably pneumatic and may be an on board compressor unit 21 supplying at least 10 LPM external cuff activation via gas tubes 26, 26a, 26b, as shown in Fig. 2. The invention, however, is not limited to use of an on board compressor unit as any adequate pressure source can be employed, 30 for example, a compressed gas (e.g., air, CO₂, oxygen, nitrogen, etc.) tank (not shown) preferably with a tank volume of 1.5 liters at 100 psi or greater for internal

pressurization. Alternatively, an internally pressurized reservoir tank (not shown) may be used.

Gas valves 22-23 are provided on the gas tube 26 to allow for control of the pressure provided by the onboard compressor unit 21. Anti-back flow valves 24a, 24b may be provided respectively on the gas tubes 26a, 26b. Pressure sensors P5, P6 may be provided respectively on the gas tubes 26a, 26b to relay conditions therein to the microprocessor 150, shown in Fig. 3. Gas valves GV_1 and GV_2 may be provided to release pressure from the cuffs 16a, 16b. One or both of gas valves GV_1 and GV_2 may be vented to the atmosphere. Gas valve GV_4 in communication with reservoir tanks 15a, 15b via tubing 18a, 18b may be provided to vent air from the reservoir tanks 15a, 15b through tubing 18. The third reservoir tank 17 is preferably pressurized by pressure released from one of the pressure cuffs via gas valve GV_2 .

The medical fluid may, for example, be a simple crystalloid solution, or may be augmented with an appropriate oxygen carrier. The oxygen carrier may, for example, be washed, stabilized red blood cells, cross-linked hemoglobin, pegolated hemoglobin or fluorocarbon based emulsions. The medical fluid may also contain antioxidants known to reduce peroxidation or free radical damage in the physiological environment and specific agents known to aid in tissue protection. As discussed in detail below, an oxygenated (e.g., cross-linked hemoglobin-based bicarbonate) solution is preferred for the normothermic mode while a non-oxygenated (e.g., simple crystalloid solution preferably augmented with antioxidants) is preferred for the hypothermic mode. The specific medical fluids used in both the normothermic and hypothermic modes are designed to prevent the washing away of or damage to the vascular endothelial lining of the organ.

The perfusion solution may be provided in a perfusion solution kit, for example, a saleable package preferably containing at least one first container holding a first perfusion solution for normothermic perfusion and at least one second container holding a second, different perfusion solution for hypothermic perfusion, optionally the box 10 shown in Fig. 2. The first perfusion solution may contain at least one oxygen carrier, may be oxygenated and/or may be selected from the group consisting of a cross-linked hemoglobin and stabilized red blood cells. The second perfusion solution may be non-oxygenated, may contain at least one anti-oxidant, and/or may contain at least one vasodilator. Additionally, the solution may contain no more than

5 mM of dissolved pyruvate salt. Also, the first container and the second container may be configured to be operably connected to a perfusion machine as perfusion fluid reservoirs in fluid communication with perfusate conduits of said perfusion machine. Further, one of the first and second containers may be compressible to apply pressure to the perfusion solution therein. Furthermore, at least one of the first and second containers may include a first opening for passage of a contained perfusion solution out of the container and a second opening passage of a compressed gas into the container. The package may be a cassette configured to be operably connected to a perfusion machine for connection of the first and second containers within the cassette in fluid communication with perfusate conduits or tubing of the perfusion machine.

The medical fluid within reservoir 10 is preferably brought to a predetermined temperature by a first thermoelectric unit 30a in heat transfer communication with the reservoir 10. A temperature sensor T3 relays the temperature within the reservoir 10 to the microprocessor 150, which adjusts the thermoelectric unit 30a to maintain a desired temperature within the reservoir 10 and/or displays the temperature on a control and display areas 5a for manual adjustment. Alternatively or in addition, and preferably where the organ perfusion device is going to be transported, the medical fluid within the hypothermic perfusion fluid reservoir can be cooled utilizing a cryogenic fluid heat exchanger apparatus such as that disclosed in co-pending application Serial No. 09/039,443, which is hereby incorporated by reference.

An organ chamber 40 is provided which supports a cassette 65, as shown in Fig. 2, which holds an organ to be perfused, or a plurality of cassettes 65,65,65, as shown in Fig. 12, preferably disposed one adjacent the other. Various embodiments of the cassette 65 are shown in Figs. 11A-11D. The cassette 65 is preferably formed of a material that is light but durable so that the cassette 65 is highly portable. The material may also be transparent to allow visual inspection of the organ.

Preferably the cassette 65 includes side walls 67a, a bottom wall 67b and an organ supporting surface 66, which is preferably formed of a porous or mesh material to allow fluids to pass therethrough. The cassette 65 may also include a top 67d and may be provided with an opening(s) 63 for tubing (see, for example, Fig. 11D). The opening(s) 63 may include seals 63a (e.g., septum seals or o-ring seals) and optionally be provided with plugs (not shown) to prevent contamination of the organ and maintain a sterile environment. Also, the cassette 65 may be provided with a closeable air vent

61 (see, for example, Fig. 11D). Additionally, the cassette 65 may be provided with tubing for connection to the organ or to remove medical fluid from the organ bath and a connection device(s) 64 for connecting the tubing to, for example, tubing 50c, 81, 82, 91 and/or 132 (see, for example, Fig. 11D). The cassette 65, and more particularly the organ support, opening(s), tubing(s) and/or connection(s), may be specifically tailored to the type of organ and/or size of organ to be perfused. Outer edges 67c of the side support walls 67a can be used to support the cassette 65 disposed in the organ chamber 40. The cassette 65 may further include a handle portion 68 which allows the cassette 65 to be easily handled, as shown, for example, in Figs. 11C and 11D. Each cassette 65 may also be provided with its own stepping motor/cam valve 65 (for example, in the handle portion 68, as shown in Fig. 11C) for fine tuning the pressure of medical fluid perfused into the organ 60 disposed therein, discussed in more detail below. The cassette 65 is configured such that it may be removed from the organ perfusion apparatus 1 and transported to another organ perfusion apparatus in a portable transport apparatus, such as, for example, a conventional cooler or a portable container such as that disclosed in simultaneously filed co-pending U.S. Application No. 09/161,919, which is hereby incorporated by reference.

When transported, the organ is disposed on the organ supporting surface 66 and the cassette 65 is preferably enclosed in a preferably sterile bag 69, as shown, for example, in Fig. 11A. When the organ is perfused with medical fluid, effluent medical fluid collects in the bag 69 to form an organ bath. Alternatively, the cassette 65 can be formed with a fluid tight lower portion in which the effluent medical fluid may collect, or the effluent medical fluid may collect in the organ chamber 40 to form the organ bath. In either alternative case, the bag 69 would preferably be removed prior to inserting the cassette into the organ chamber 40. Further, where a plurality of organs are to be perfused, an organ chamber may be provided for each organ.

The organ bath is preferably cooled to a predetermined temperature by a second thermoelectric unit 30b in heat transfer communication with the organ chamber 40. Alternatively and preferably where the organ perfusion device is going to be transported, the medical fluid within reservoir 10 can be cooled utilizing a cryogenic fluid heat exchanger apparatus such as that disclosed in co-pending application Serial No. 09/039,443, which is hereby incorporated by reference. A temperature sensor T2 within the organ chamber 40 relays the temperature of the organ 60 to the

microprocessor 150, which adjusts the thermoelectric unit 30b to maintain a desired organ temperature and/or displays the temperature on the control and display areas 5c for manual adjustment.

Medical fluid may be fed from the bag 15a directly to an organ 60 disposed in the organ chamber 40 through tubing 50a, 50b, 50c or from bag 15b through tubing 50d, 50e, 50c by opening valve LV₄ or LV₃, respectively. Conventional medical fluid bag and tubing connections are utilized. All tubing is disposable, easily replaceable and interchangeable. Further, all tubing is formed of or coated with materials compatible with the medical fluids used, more preferably non-thrombogenic materials. An end of the tubing 50c is inserted into the organ 60. The tubing is connected to the organ(s) with conventional methods, for example, with sutures. The tubing may include a lip to facilitate connection to the organ. However, the specific methods and connection depend on the type of organs(s) to be perfused.

The microprocessor 150 preferably controls the pressure source 20 in response to signals from the pressure sensor P1 to control the pressure of the medical fluid fed into the organ 60. The microprocessor 150 may display the pressure on the control and display areas 5a, optionally for manual adjustment. A fluid flow monitor F1 may also be provided on the tubing 50c to monitor the flow of medical fluid entering the organ 60 to indicate, for example, whether there are any leaks present in the organ.

Alternatively, the medical fluid may be fed from the reservoir tank 17 via tubing 51 into an intermediary tank 70 preferably having a pressure head of approximately 5 to 40 mm Hg. Medical fluid is then fed by gravity from the intermediary tank 70 to the organ 60 along tubing 50c by activating a valve LV₆. A level sensor 71 is provided in the intermediary tank 70 in order to maintain the pressure head. Where a plurality of organ chambers 40 and organs 60 are provided, the organs 60 are connected in parallel to the reservoir 10 utilizing suitable tubing duplicative of that shown in Fig. 2. See, for example, Fig. 12. The use of pneumatically pressurized and gravity fed fluid pumps configured to avoid overpressurization even in cases of system failure prevents general tissue damage to the organ and the washing away of or damage to the vascular endothelial lining of the organ. Thus, organ perfusion in this system can be performed with either hydrostatic perfusion (gravity fed flow) or peristaltic perfusion by introducing flow to the organ from a peristaltic (roller) pump.

A bubble detection system may be installed to sense bubbles in the perfusate. An air sensor and sensor board are preferably used. The output of the sensor activates a debubbler system, such as an open solenoid valve, to rid bubbles from the perfusate flow prior to organ introduction. As with all of the sensors and detectors in this system, the bubble detector may be positioned at any point in the system that is effective based on the particular parameters or design characteristics of the system. For example, a bubble detector and debubbler system BD may be positioned between the cam valve 205 and pressure sensor P1, as shown in Fig. 1.

A stepping motor/cam valve 205 may be arranged on the tubing 50c to provide pulsatile delivery of the medical fluid to the organ 60, to decrease the pressure of the medical fluid fed into the organ 60, and/or to stop flow of medical fluid into the organ 60 if the perfusion pressure exceeds a predetermined amount. Specific embodiments of the stepping motor/cam valve are shown in Figs. 13A-13B and 14A-14F. Figs. 13A-13B show a stepping motor/rotational type cam valve.

Fig. 13A is a top view of the apparatus. Tubing, for example, tubing 50c, is interposed between a support 203 and cam 200. Cam 200 is connected by a rod 201 to stepping motor 202. Fig. 13B is a side view of the apparatus. The dashed line shows the rotational span of the cam 200. In Fig. 13B, the cam 200 is in its non-occluding position. Rotated 180 degrees, the cam 200 totally occludes the tubing 50c with varying degrees of occlusion therebetween. This stepping motor/cam valve is relatively fast, for example, with respect to the embodiment shown in Figs. 14A - 14F; however, it requires a strong stepping motor.

Figs. 14A - 14F disclose another stepping motor/cam valve 210 according to the invention. Fig. 14A is a side view of the apparatus while Fig. 14C is a top view. Tubing, for example, tubing 50c, is interposed between cam 220 and support 223. The cam 220 is connected to stepping motor 222 by supports 221a - 221d and helical screw 225, which is connected to the stepping motor 222 via plate 222a. Fig. 14B shows the supports 221a and plate 222a in front view. As shown in Fig. 14D, where the support 221d is to the left of the center of the helical screw 225, the tubing 50c is not occluded. However, as the helical screw 225 is turned by the stepping motor 222, the support 221d moves to the left (with respect to Figs. 14D - 14F) toward a position where the cam 220 partially or fully occludes the tubing 50c. Such apparatus is slower than the apparatus of Figs. 13A - 13B, but is more energy efficient.

Medical fluid expelled from the organ 60 which has collected in the bottom of the bag 69 (the cassette 65 or the organ chamber 40) is either pumped out through tubing 81 by a pump 80 for filtration, passing through a filter unit 82 and being returned to the organ bath, or is pumped out by a pump 90 for circulation through tubing 91. The pumps 80, 90 are preferably conventional roller pumps; however, other types of pumps may also be appropriate. A level sensor L2 in communication with the microprocessor 150 ensures that a predetermined level of effluent medical fluid is maintained within the organ chamber 40. A temperature sensor T1 disposed in the tubing 91 relays the temperature of the medical fluid pumped out of the organ bath along tubing 91 to the microprocessor 150, which monitors the same. A pressure sensor P2 disposed along the tubing 91 relays the pressure therein to the microprocessor 150, which shuts down the system if the fluid pressure in the tubing 91 exceeds a predetermined limit, or activates an alarm to notify the operator that the system should be shut down, for example, to clean filters or the like.

As the medical fluid is pumped along tubing 91 it passes through a filter unit 95 (e.g., 25 μ , 8 μ , 2 μ , 0.8 μ , 0.2 μ and/or 0.1 μ filters); a CO₂ scrubber/O₂ membrane 100 and an oxygenator 110, for example, a JOSTRA™ oxygenator. The CO₂ scrubber/O₂ membrane 100 is preferably a hydrophobic macroporous membrane with a hydrophilic (e.g., Hypol) coating in an enclosure. A vacuum source (not shown) is utilized to apply a low vacuum on a side opposite the hydrophilic coating by the activation of valve VV₁. A hydrostatic pressure of approximately 100 mm Hg is required for aqueous passage through the membrane. The mechanical relief valve (not shown) prevents the pressure differential from attaining this level. Immobilized pegolated carbonic anhydrase may be included in the hydrophilic coating. This allows bicarbonate to be converted to CO₂ and subsequently removed by vacuum venting. However, with organs such as kidneys which have the ability to eliminate bicarbonate, this may be unnecessary except in certain cases.

The oxygenator 110 is preferably a two stage oxygenator which preferably includes a hydrophilically coated low porosity oxygen permeable membrane. A portion of the medical fluid is diverted around the oxygenator along tubing 111 in which is disposed a viability sensor V1, which senses fluid characteristics, such as organ resistance (pressure/flow), pH, pO₂, pCO₂, LDH, T/GST and/or Tprotein, indicative of an organ's viability. The viability sensor V1 is in communication with

the microprocessor 150 and allows the organ's viability to be assessed either automatically or manually. One of two gases, preferably 100% oxygen and 95/5% oxygen/carbon dioxide, is placed on the opposite side of the membrane depending on the pH level of the diverted medical fluid. Alternatively, another pump (not shown) may be provided which pumps effluent medical fluid out of the organ chamber 40 and through a viability sensor before returning it to the bath, or the viability sensor can be placed on tubing 81 utilizing pump 80.

Alternative to the pump 90, filter unit 95, the CO₂ scrubber/O₂ membrane 100 and/or the oxygenator 110, a modular combined pump, filtration, oxygenation and/or debubbler apparatus may be employed such as that described in detail in simultaneously filed co-pending U.S. Patent Application No. 09/039,318, which is hereby incorporated by reference. As shown in Figs. 4 - 10, the apparatus 5001 is formed of stackable modules. The apparatus 5001 is capable of pumping a fluid through a system as well as oxygenating, filtering and/or debubbling the fluid. The modules are each formed of a plurality of stackable support members and are easily combinable to form a compact apparatus containing desired components. Filtration, oxygenation and/or degassing membranes are disposed between the support members.

Figures 4-8 show various modules that may be stacked to form a combined pump, filtration, oxygenation and/or debubbler apparatus, such as the combined pump, filtration, oxygenation and debubbler apparatus 5001 shown in Figs. 9-10. As depicted in these figures, the combined pump, filtration, oxygenation and debubbler apparatus 5001 is preferably formed of a plurality of stackable support members groupable to form one or more modules.

Interposed between the plurality of stackable support member are filtration, oxygenation and/or degassing membranes depending on a particular user's needs. The filtration, oxygenation and/or degassing membranes are preferably commercially available macro-reticular hydrophobic polymer membranes hydrophilically grafted in a commercially known way, such as, for example, ethoxylation, to prevent protein deprivation, enhance biocompatibility with, for example, blood and to reduce clotting tendencies. The filtration membrane(s) is preferably hydrophilically grafted all the way through and preferably has a porosity (pore size) within a range of 15 to 35 μ , more preferably 20 to 30 μ , to filter debris in a fluid, preferably without filtering out cellular or molecular components of the fluid. The degassing membrane(s) and

oxygenation membrane(s) are hydrophilically surface treated to maintain a liquid-gas boundary. The degassing membrane(s) and oxygenation membrane(s) preferably have a porosity of 15 μ or less, more preferably 10 μ or less.

5 The modules may include a first pump module 5010, as shown in exploded view in Fig. 4; a filtration module 5020, as shown in exploded view in Fig. 5; an oxygenation module 5030, as shown in exploded view in Fig. 6; a debubbler module 5040, as shown in exploded view in Fig. 7; and a second pump module 5050, as shown in exploded view in Fig. 8. The pump modules are each connected to a source of pump fluid and are actuated either manually or by the microprocessor. The support
10 members are preferably similarly shaped. For example, the support members may each be plate-shaped; however, other shapes may also be appropriate. As shown in Fig. 10, the support members are preferably removably connected by screws or bolts 5065; however, other fasteners for assembling the apparatus may also be appropriate.

The first pump module 5010 preferably includes a first (end) support member
15 5011, a second support member 5012 with a cut-out center area 5012c, a diaphragm 5013 and a third support member 5014. The support members of this module and each of the other modules are preferably thin and substantially flat (plate-like), and can be formed of any appropriate material with adequate rigidity and preferably also biocompatibility. For example, various resins and metals may be acceptable. A
20 preferred material is an acrylic/polycarbonate resin.

The first (end) support member 5011 is preferably solid and provides support for the pump module 5010. The first (end) support member 5011 preferably includes a domed-out cavity for receiving pump fluid such as air. Tubing 5011t is provided to allow the pump fluid to enter the pump module 5010. The diaphragm 5013 may be
25 made of any suitable elastic and preferably biocompatible material, and is preferably polyurethane. The third support member 5014 includes a domed-out fluid cavity 5014d and tubing 5014t for receiving fluid, such as, for example, blood or an artificial perfusate, into the cavity 5014d of the pump module 5010. The first pump module, or any of the other modules, may also include a port 5014p for sensors or the like.
30 Preferably hemocompatible anti-backflow valves serve to allow unidirectional flow through the pump module 5010.

The filtration module 5020 preferably includes a filtration membrane 5021m which forms a boundary of cavity 5014d, a first support member 5022 with a cut-out

center area 5022c, a degassing membrane 5022m and second and third support members 5023 and 5024. The filtration membrane 5021m is preferably a 25μ macro-reticular filtration membrane modified to enhance biocompatibility with, for example, blood and to reduce clotting tendencies (like the other supports, filters and membranes in the device). The degassing membrane 5022m is preferably a $0.2 - 3\mu$ macro-reticular degassing membrane with a reverse flow aqueous pressure differential of at least 100 mmHg for CO_2 removal surface modified to enhance biocompatibility.

The first support 5022 includes tubing 5022t for forwarding fluid into the oxygenation module 30, or another adjacent module, if applicable, after it has passed through the filtration membrane 5021m and along the degassing membrane 5022m. The second support member 5023 of the filtration module 5020 includes a domed-out fluid cavity 5023d and tubing 5023t through which a vacuum may be applied to the cavity 5023d to draw gas out of the fluid through degassing membrane 5022m. The fourth support member 5024 is preferably solid and provides support for the filtration module 5020. The third support member can also include tubing 5024t through which a vacuum may be applied to draw gas out of the fluid through the degassing membrane 5031m of the oxygenation module 5030 as discussed below. The filtration module 5020, or any of the other modules, may also include a port 5023p for sensors or the like.

The oxygenation module 5030 includes a degassing membrane 5031m, a first support member 5032, a filtration membrane 5033m, an oxygenation membrane 5034m, a second support member 5034 with a cut-out center area 5034c, and third and fourth support members 5035, 5036. The degassing membrane 5031m is preferably a $0.2 - 3\mu$ macro-reticular degassing membrane with a reverse flow aqueous pressure differential of at least 100 mmHg surface modified to enhance biocompatibility.

The first support member 5032 includes a domed-out fluid cavity 5032d. The surface of the domed-out fluid cavity 5032d preferably forms a tortuous path for the fluid, which enhances the oxygenation and degassing of the fluid. The filtration membrane 5033m is preferably a 25μ macro-reticular filtration membrane modified to enhance biocompatibility. The oxygenation membrane 5034m is preferably a $0.2 - 1\mu$ macro-reticular oxygenation membrane with a reverse flow aqueous pressure differential of at least 100 mmHg surface modified to enhance biocompatibility.

The second support member 5034 includes tubing 5034t for forwarding fluid out of the oxygenation module 5030 into the debubbler module 5040, or another adjacent module, if applicable. The third support member 5035 includes a domed-out cavity 5035d and tubing 5035t for receiving oxygen from an external source. The
5 fourth support member 5036 is preferably solid and provides support for the oxygenation module 5030.

The debubbler module 5040 includes a first support member 5041, a filtration membrane 5042m, a degassing membrane 5043m, a second support member 5043 having a cut-out center area 5043c, and a third support member 5044. The first
10 support member 5041 has a domed-out fluid cavity 5041d.

The filtration membrane 5042m is preferably a 25 μ macro-reticular filtration membrane modified to enhance biocompatibility. The degassing membrane 5043m is preferably a 0.2 - 3 μ macro-reticular degassing membrane with a reverse flow aqueous pressure differential of at least 100 mmHg surface modified to enhance
15 biocompatibility. The second support member 5043 has tubing 5043t for forwarding fluid out of the debubbler module 5040 into the pump module 5050, or another adjacent module, if applicable. The third support member 5044 includes a domed-out cavity 5044d and tubing 5044t through which a vacuum may be applied to draw gas out of the fluid through the degassing membrane 5043m.

The second pump module 5050 may correspond to the first pump
20 module 5010. It preferably includes a first support member 5051, a diaphragm 5052, a second support member 5053 with a cut-out center area 5053c, and a third (end) support member 5054. The first support member 5051 includes a domed out fluid cavity 5051d and tubing 5051t for allowing fluid to exit the pump module. The
25 diaphragm 5052 is preferably a polyurethane bladder.

The third (end) support piece member 5054 is preferably solid and provides support for the pump module 5050. Support member 5054 preferably includes a domed out cavity (not shown) for receiving pump fluid. Tubing 5054a is provided to allow the pump fluid such as air to enter the pump module 5050. Preferably
30 hemocompatible anti-backflow valves may serve to allow unidirectional flow through the pump module 5050.

In operation, blood and/or medical fluid enters the first pump module 5010 through tube 5014t passes through the filtration membrane 5021m and along the

degassing membrane 5022m. A small vacuum is applied through tubing 5023t to draw gas through the degassing membrane 5022m. Next, the blood and/or medical fluid travels into the oxygenation module 5030 via internal tubing 5022t, passing along the degassing membrane 5031m, through the filtration membrane 5033m and along the oxygenation membrane 5034m. Oxygen is received into the domed-out cavity 5035d of the third support member of the oxygenation module 5030 via tubing 5035t and passes through the oxygenation membrane 5034m into the blood and/or medical fluid as the blood and/or medical fluid travels along its surface.

After being oxygenated by the oxygenation module 5030, the blood and/or medical fluid then travels via internal tubing 5034t into the debubbler module 5040. The blood and/or medical fluid passes through the filtration membrane 5042m and along the degassing membrane 5043m. A small vacuum force is applied through tubing 5044t to draw gas out of the blood and/or medical fluid through the degassing membrane 5043m. After passing through the degassing module 5040, the blood and/or medical fluid travels into the second pump module 5050 through tubing 5041t, and exits the second pump module 5050 via tubing 5051t.

After passing through the oxygenator 110, or alternatively through the combined pump, oxygenation, filtration and/or degassing apparatus 5001, the recirculated medical fluid is selectively either directed to the reservoir 15a or 15b not in use along tubing 92a or 92b, respectively, by activating the respective valve LV_2 and LV_3 on the tubing 92a or 92b, or into the organ chamber 40 to supplement the organ bath by activating valve LV_1 . Pressure sensors P3 and P4 monitor the pressure of the medical fluid returned to the bag 15a or 15b not in use. A mechanical safety valve MV_2 is provided on tubing 91 to allow for emergency manual cut off of flow therethrough. Also, tubing 96 and manual valve MV_1 are provided to allow the apparatus to be drained after use and to operate under a single pass mode in which perfusate exiting the organ is directed to waste rather than being recirculated (recirculation mode.)

A bicarbonate reservoir 130, syringe pump 131 and tubing 132, and an excretion withdrawal unit 120, in communication with a vacuum (not shown) via vacuum valve VV_2 , and tubing 121a, 122a are also each provided adjacent to and in communication with the organ chamber 40.

The method according to the invention preferably utilizes apparatus such as that discussed above to perfuse an organ to sustain, monitor and/or restore the viability of an organ and/or to transport and/or store the organ. Preservation of the viability of an organ is a key factor to a successful organ transplant. Organs for transplant are often deprived of oxygen (known as ischemia) for extended periods of time due to disease or injury to the donor body, during removal of the organ from the donor body and/or during storage and/or transport to a donee body. The method according to the present invention focuses on three concepts in order to preserve an organ's viability prior to transplant of the organ into a donor body -- treating the cellular mitochondria to maintain and/or restore pre-ischemia energy and enzyme levels, preventing general tissue damage to the organ, and preventing the washing away of or damage to the vascular endothelial lining of the organ.

The mitochondria are the energy source in cells. They need large amounts of oxygen to function. When deprived of oxygen, their capacity to produce energy is reduced or inhibited. Additionally, at temperatures below 20 °C the mitochondria are unable to utilize oxygen to produce energy. By perfusing the organ with an oxygen rich medical fluid at normothermic temperatures, the mitochondria are provided with sufficient amounts of oxygen so that pre-ischemia levels of reserve high energy nucleotide, that is, ATP levels, in the organ reduced by the lack of oxygen are maintained and/or restored along with levels of enzymes that protect the organ's cells from free radical scavengers. Pyruvate rich solutions, such as that disclosed in U.S. Patent No. 5,066,578, are incapable of maintaining and/or restoring an organ's pre-ischemia energy levels and only function in the short term to raise the level of ATP a small amount. That is, organs naturally have significant pyruvate levels. Providing an organ with additional pyruvate will not assist in restoring and/or maintaining the organ's pre-ischemia energy levels if the mitochondria are not provided with sufficient oxygen to produce energy. Thus, the normothermic perfusion fluid may contain pyruvate but may also contain little or no pyruvate. For example, it can contain less than 6 mM of pyruvate, 5 mM, 4 mM, or even no pyruvate. Other known preservation solutions, such as that disclosed in U.S. Patent No. 5,599,659, also fail to contain sufficient oxygen to restore and/or maintain pre-ischemia energy and enzyme levels.

After maintaining and/or restoring the organ's pre-ischemia energy levels by perfusing the organ with an oxygen rich first medical fluid at normothermic or near-normothermic temperatures (the normothermic mode), the organ is perfused with a second medical fluid at hypothermic temperatures (the hypothermic mode). The hypothermic temperatures slow the organ's metabolism and conserve energy during storage and/or transport of the organ prior to introduction of the organ into a donee body. The medical fluid utilized in the hypothermic mode contains little or no oxygen, which cannot be utilized by mitochondria to produce energy below approximately 20°C. The medical fluid may include antioxidants and other tissue protecting agents, such as, for example, ascorbic acid, glutathione, water soluble vitamin E, catalase, or superoxide dismutase to protect against high free radical formation which occurs at low temperatures due to the reduction in catalase/superoxide dismutase production. Further, various drugs and agents such as hormones, vitamins, nutrients, antibiotics and others may be added to either solution where appropriate. Additionally, vasodilators, such as, for example, peptides, may be added to the medical fluid to maintain flow even in condition of injury.

Prior to normothermic perfusion with the oxygen rich first medical fluid at normothermic temperatures, the organ may be flushed with a medical solution containing little or no oxygen and preferably containing antioxidants. The flushing may be performed at either normothermic, near-normothermic or hypothermic temperatures.

The organ may be perfused at normothermic or near-normothermic temperatures to sustain, monitor and/or restore its viability prior to being perfused at hypothermic temperatures for storage and then may be transported without or preferably with hypothermic perfusion. Also, the normothermic perfusion may be performed in vivo prior to removal of the organ from the donor body. Further, the organ may be perfused at normothermic temperatures to sustain, monitor and/or restore its viability prior to being perfused at hypothermic temperatures preparatory to storage and/or transport. Then the organ may be transplanted into a donee body while remaining at hypothermic temperatures, or it may first be subjected to normothermic perfusion to help it recover from the effects of storage and/or transport. In the latter case, it may then be transplanted at normothermic temperatures, or preferably, be hypothermically perfused again for transplantation at hypothermic temperatures.

After transplant, the organ may optionally again be perfused at normothermic temperatures in vivo, or allowed to warm up from the circulation of the donee.

5 The organ cassette according to the present invention allows an organ(s) to be easily transported to an organ recipient and/or between organ perfusion apparatus in a portable transport apparatus, such as, for example, a conventional cooler or a portable container such as that disclosed in co-pending U.S. Application No. 09/161,919. Because the organ cassette may be provided with openings to allow the insertion of tubing of an organ perfusion apparatus into the cassette for connection to an organ disposed therein, or may be provided with its own tubing and connection device or
10 devices to allow connection to tubing from an organ perfusion apparatus and/or also with its own valve; it provides a protective environment for an organ for storage and/or transport while facilitating insertion of the organ into and/or connection of an organ to the tubing of an organ perfusion device. Further, the organ cassette may also include a handle to facilitate transport of the cassette and may be formed of a transparent material
15 so the organ may be visually monitored.

Optionally, the apparatus may include a Global Positioning System (GPS) (not shown) to allow tracking of the location of the organ(s). The apparatus may also include a data logger and/or transmitter (not shown) to allow monitoring of the organ(s) at the location of the apparatus or at another location.

20 The method of the invention will be discussed below in terms of the operation of the apparatus shown in Fig. 2. However, other apparatus may be used to perform the inventive method.

As previously discussed, the apparatus discussed above can operate in two modes: a normothermic perfusion mode and a hypothermic perfusion mode. The
25 normothermic perfusion mode will be discussed first followed by a discussion of hypothermic perfusion mode. Repetitive description will be omitted.

In the normothermic or near-normothermic perfusion mode, an organ is perfused for preferably $\frac{1}{2}$ to 6 hours, more preferably $\frac{1}{2}$ to 4 hours, most preferably $\frac{1}{2}$ to 1 hour, with a medical fluid maintained preferably within a range of approximately
30 15°C (for example, room temperature) to 38°C, more preferably 18°C to 35°C, most preferably 18°C to 25°C by the thermoelectric unit 30a disposed in heat exchange communication with the medical fluid reservoir 10.

As discussed above, in this mode, the medical fluid is preferably an oxygenated cross-linked hemoglobin-based bicarbonate solution. Cross-linked hemoglobin-based medical fluids can deliver up to 150 times more oxygen to an organ per perfusate volume than, for example, a simple University of Wisconsin (UW) gluconate type perfusate. This allows normothermic perfusion for one to two hours to partially or totally restore depleted ATP levels. However, the invention is not limited to this preservation solution. Other preservation solutions, such as those disclosed in U.S. Patents Nos. 5,149,321, 5,234,405 and 5,395,314 and co-pending U.S. Patent Application No. 08/484,601, which are hereby incorporated by reference, may also be appropriate.

In the normothermic perfusion mode, the medical fluid is fed directly to an organ disposed within the organ chamber 40 from one or the other of bags 15a, 15b via tubing 50a, 50b, 50c or 50d, 50e, 50c, respectively. The organ is perfused at flow rates preferably within a range of approximately 3 to 5 ml/gram/min. Pressure sensor P1 relays the perfusion pressure to the microprocessor 150, which varies the pressure supplied by the pressure source 20 to control the perfusion pressure and/or displays the pressure on the control and display areas 5a for manual adjustment. The pressure is preferably controlled within a range of approximately 10 to 100 mm Hg, preferably 50 to 90 mm Hg, by the combination of the pressure source 20 and pressure cuff 15a, 15b in use and the stepping motor/cam valve 65. The compressor and cuffs provide gross pressure control. The stepping motor/cam valve 65, which is also controlled by the operator, or by the microprocessor 150 in response to signals from the pressure sensor P1, further reduces and fine tunes the pressure and/or puts a pulse wave on the flow into the organ 60. If the perfusion pressure exceeds a predetermined limit, the stepping motor/cam valve 65 may be activated to shut off fluid flow to the organ 60.

The specific pressures, flow rates and length of perfusion time at the particular temperatures will vary depending on the particular organ or organs being perfused. For example, hearts and kidneys are preferably perfused at a pressure of approximately 10 to 100 mm Hg and a flow rate of approximately 3 to 5 ml/gram/min. for up to approximately 2 to 4 hours at normothermic temperatures to maintain and/or restore the viability of the organ by restoring and/or maintaining pre-ischemia energy levels of the organ, and are then preferably perfused at a pressure of approximately 10 to 30 mm Hg and a flow rate of approximately 1 to 2 ml/gram/min.

for as long as approximately 72 hours to 7 days at hypothermic temperatures for storage and/or transport. However, these criteria will vary depending on the condition of the particular organ, the donor body and/or the donee body and/or on the size of the particular organ. One of ordinary skill in the art can select appropriate conditions without undue experimentation in view of the guidance set forth herein.

Effluent medical fluid collects in the bottom of the organ chamber 40 and is maintained within a range of approximately 20°C to 38°C, preferably 25°C to 37°C, more preferably 25 to 35°C by the second thermoelectric unit 30b. The temperature sensor T2 relays the organ temperature to the microprocessor 150, which controls the thermoelectric unit 30a to adjust the temperature of the medical fluid and organ bath to maintain the organ 60 at the desired temperature, and/or displays the temperature on the control and display areas 5c for manual adjustment.

Collected effluent medical fluid is pumped out by the pump 80 via tubing 81 through the filter unit 82 and then returned to the organ bath. This filters out surgical and/or cellular debris from the effluent medical fluid and then returns filtered medical fluid to act as the bath for the organ 60. Once the level sensor L2 senses that a predetermined level of effluent medical fluid is present in the organ chamber 40 (preferably enough to maintain the organ 60 immersed in effluent medical fluid), additional effluent medical fluid is pumped out by the pump 90 through tubing 91. The temperature sensor T1 relays the temperature of the organ bath to the microprocessor 150, which controls the thermoelectric unit 30b to adjust the temperature of the medical fluid to maintain the organ 60 at the desired temperature and/or displays the temperature on the control and display area 5c for manual adjustment and monitoring.

As noted above, the medical fluid can be directed to waste in a single pass mode or recirculated eventually back to the organ and/or bath (recirculation mode.)

Along tubing 91, the recirculated medical fluid is first pumped through the filter unit 95. Use of a cross-linked hemoglobin medical fluid allows the use of sub-micron filtration to remove large surgical debris and cellular debris, as well as bacteria. This allows the use of minimal antibiotic levels, aiding in preventing organ damage such as renal damage.

Next, the recirculated medical fluid is pumped through the CO₂ scrubber/O₂ membrane 100. The medical fluid passes over the hydrophobic macroporous

membrane with a hydrophilic coating (for example, Hypol) and a low vacuum is applied on the opposite side by activating valve VV_1 which removes CO_2 from the recirculated medical fluid.

Subsequently, a portion of the medical fluid then enters the oxygenator 110 (for example, a JOSTRA™ oxygenator) and a portion is diverted therearound passing via tubing 111 through the pH, pO_2 , pCO_2 , LDH, T/GST and Tprotein sensor V_1 . At this point two gases, preferably 100% oxygen and 95/5% oxygen/carbon dioxide, are respectively placed on the opposite sides of the membrane depending on the pH level of the diverted medical fluid. The gases are applied at a pressure of up to 200 mm Hg, preferably 50 to 100 mm Hg, preferably through a micrometer gas valve GV_3 . The cross-linked hemoglobin-based bicarbonate medical fluid may be formulated to require a pCO_2 of approximately 40 mm Hg to be at the mid point (7.35) of a preferred pH range of 7.25-7.45.

If the medical fluid exiting the oxygenator is within the preferred pH range (e.g., 7.25-7.45), 100% oxygen is delivered to the gas exchange chamber, and valve LV_1 is then not opened, allowing the perfusate to return to the reservoir 10 into the bag 15a or 15b not in use. If the returning perfusate pH is outside the range on the acidic side (e.g., less than 7.25), 100% oxygen is delivered to the gas exchange chamber and valve LV_1 is then opened allowing the perfusate to return to the organ chamber 40. Actuation of syringe pump 131 pumps, for example, one cc of a bicarbonate solution from the bicarbonate reservoir 130, via tubing 132 into the organ bath. Medical fluids with high hemoglobin content provide significant buffering capacity. The addition of bicarbonate aids in buffering capacity and providing a reversible pH control mechanism.

If the returning perfusate pH is outside the range on the basic side (e.g., greater than 7.25), 95/5% oxygen/carbon dioxide is delivered to the gas exchange chamber and valve LV_1 is not actuated, allowing the perfusate to return to the bag 15a or 15b not in use. The bag 15a or 15b not in use is allowed to degas (e.g., any excess oxygen) through valve GV_4 . When the bag 15a or 15b in use has approximately 250ml or less of medical fluid remaining therein, its respective cuff 16a, 16b is allowed to vent via its respective gas valve GV_1 , GV_2 . Then, the respective cuff 16a, 16b of the bag 15a or 15b previously not in use is supplied with gas from the

compressed gas source 20 to deliver medical fluid to the organ to continue perfusion of the organ.

In the hypothermic mode, an organ is perfused with a cooled medical fluid, preferably at a temperature within a range of approximately 1°C to 15°C, more preferably 4 °C to 10 °C, most preferably around 10 °C. The medical fluid is
5 preferably a crystalloid perfusate without oxygenation and preferably supplemented with antioxidants and other tissue protecting agents, such as, for example, ascorbic acid, glutathione, water soluble vitamin E, catalase, or superoxide dismutase.

Instead of feeding the medical fluid directly to the organ, the medical fluid
10 may be fed from the reservoir tank 17 via tubing 51 into an intermediary tank 70 preferably having a pressure head of approximately 5 to 40 mm Hg, more preferably 10 to 30 mm Hg, most preferably around 20 mm Hg. Medical fluid is then fed by gravity from the intermediary tank 70 to the organ 60 along tubing 50c by activating a valve LV₆. The level sensor 71 in the intermediary tank 70 is used to control the feed
15 from reservoir tank 17 to maintain the desired pressure head. Because the medical fluid is fed to the organ by gravity in the hypothermic mode, there is less perfusion pressure induced damage to the delicate microvasculature of the organ. In fact, the pressure at which the organ is perfused is limited by the pressure head to at most 40 mm Hg.

20 The stepping motor/cam valve 205 may be arranged on the tubing 50c to provide pulsatile delivery of the medical fluid to the organ 60, to decrease the pressure of the medical fluid fed into the organ 60 for control purposes, or to stop flow of medical fluid into the organ 60, as described above.

Further, in the hypothermic mode, because the organ 60 has less of a demand
25 for nutrients, the medical fluid may be provided to the organ 60 intermittently (e.g., every two hours at a flow rate of up to approximately 100 ml/min.), or at a slow continuous flow rate (e.g., up to approximately 100 ml/min.) over a long period of time. Intermittent perfusion can be implemented in the single pass mode or recirculation mode. The pump 80, filter unit 82 and tube 81 may be used to filter the
30 organ bath along with use of the pH, pO₂, pCO₂, LDH, T/GST and Tprotein sensor; however, because the organ is unable to utilize oxygen at hypothermic temperatures, the oxygenator is not used.

Both the perfusate flow and the temperature regulation can be automatically controlled. Such automatic control allows a rapid and reliable response to perfusion conditions during operation. Automatic flow control can be based on the parameters measured from the system, including the perfusate flow rate, the perfusate pH exiting the organ, the organ inlet pressure or timed sequences such as pre-selected flow rates or switching between perfusate modes. Preferably, the flow control is based on pressure monitoring of the perfusate inflow into the organ. The benefits of automatic flow control include maintaining proper oxygenation and pH control while operating under continuous flow or controlled intermittent flow. Thermal control of the thermoelectric devices (TED) can regulate the temperature of the organ cassette or container and the perfusate reservoir. The thermal control is based on thermal measurements made for example by thermistor probes in the perfusate solution or inside the organ or by sensors in the TED.

The automatic control is preferably effected by an interactive control program using easily operated menu icons and displays. The parameters may be prestored for selection by a user or programmed by the user during operation of the system. The control program is preferably implemented on a programmed general purpose computer. However, the controller can also be implemented on a special purpose computer, a programmed microprocessor or microcontroller and peripheral integrated circuit elements, an ASIC or other integrated circuit, a digital signal processor, a hardwired electronic or logic circuit such as a discrete element circuit, a programmable logic device such as a PLD, PLA, FPGA or PAL, or the like. In general, any device capable of implementing a finite state machine that is in turn capable of implementing the control process described herein may be used. The control program is preferably implemented using a ROM. However, it may also be implemented using a PROM, an EPROM, an EEPROM, an optical ROM disk, such as a CD-ROM or DVD-ROM, and disk drive or the like. However, if desired, the control program may be employed using static or dynamic RAM. It may also be implemented using a floppy disk and disk drive, a writable optical disk and disk drive, a hard drive, flash memory or the like.

In operation, as seen in Fig. 15, the basic steps of operation to control perfusion of one or more organs include first inputting organ data. The organ data includes at least the type of organ and the mass. Then, the program will prompt the user to select one or more types of perfusion modes. The types of perfusion modes,

discussed above, include hypothermic perfusion, normothermic perfusion, and sequential perfusion using both normothermic and hypothermic perfusion. When both normothermic and hypothermic perfusion are employed, the user can select between medical fluids at different temperatures. Of course, the system includes default values
5 based on previously stored values appropriate for the particular organ. The user may also select intermittent perfusion, single pass perfusion, and recirculation perfusion. Depending on the type of perfusion selected, aerobic or anaerobic medical fluids may be specified.

Next, the type of flow control for each selected perfusion mode is set. The
10 flow control selector selects flow control based on at least one of perfusate flow rate, perfusate pH, organ inlet pressure and timed sequences. In the preferred embodiment, the flow control is based on detected pressure at the perfusion inlet to the organ. The flow of the medical fluid is then based on the selected perfusion mode and flow control.

15 During operation the conditions experienced by the system, in particular by the organ and the perfusate, are detected and monitored. The detected operating conditions are compared with prestored operating conditions. A signal can then be generated indicative of organ viability based on the comparison. The various detectors, sensors and monitoring devices are described above, but include at least a
20 pressure sensor, a pH detector, an oxygen sensor and a flow meter.

The control system may also include a thermal controller for controlling temperature of at least one of the perfusate and the organ. The thermal controller can control the temperature of the medical fluid reservoirs and the organ container by controlling the TEDs. As noted above, temperature sensors are connected to the
25 controller to facilitate monitoring and control.

The control system may be manually adjusted at any time or set to follow default settings. The system includes a logic circuit to prevent the operator from setting parameters that would compromise the organ's viability. As noted above, the system may also be operated in a manual mode for sequential hypothermic and/or
30 normothermic perfusion, as well as in the computer controlled mode for sequential hypothermic and/or normothermic perfusion.

The above described apparatus and method may be used for child or small organs as well as for large or adult organs with modification as needed of the cassettes

and or of the pressures and flow rates accordingly. As previously discussed, the organ cassette(s) can be configured to the shapes and sizes of specific organs or organ sizes. The apparatus and method can also be used to provide an artificial blood supply to, such, for example, artificial placentas cell cultures, for growing/cloning organ(s).

5 While the invention has been described in conjunction with a specific embodiment thereof, it is evident that many alternatives, modifications and variations may be apparent to those skilled in the art. Accordingly, the preferred embodiment of the invention as set forth herein is intended to be illustrative, not limiting. Various changes may be made without departing from the spirit and scope of the invention as
10 defined in the following claims.

WHAT IS CLAIMED IS:

1. A method of maintaining and/or restoring the viability of at least one organ subjected to a period of ischemia, comprising:
perfusing said at least one organ with a first medical fluid at a first
5 temperature to at least one of maintain and restore pre-ischemia ATP and enzyme levels in the organ, wherein the first medical fluid contains oxygen in an amount effective to cause the organ's mitochondria to at least one of maintain and restore pre-ischemia ATP levels in the organ; and,
at least one of storing and transporting the organ in an organ cassette after
10 perfusion of the organ with the first medical fluid at the first temperature, the organ cassette including a portable housing, an organ supporting surface, and tubing connectable to the organ to allow perfusion of the organ.
2. The method of claim 1, wherein the first medical fluid is formulated to avoid injuring the vascular endothelial lining of the organ.
- 15 3. The method of claim 1, wherein the first medical fluid is an oxygenated hemoglobin-based solution.
4. The method of claim 1, wherein the first temperature is at least about 15°C.
5. The method of claim 1, further comprising monitoring the viability of
20 the organ during said perfusing step.
6. The method of claim 1, wherein the organ is perfused at least one of intermittently and continuously at the first temperature at a pressure within a range of approximately 40 to 100 mm Hg.
7. The method of claim 1, wherein the organ is perfused at the first
25 temperature utilizing a perfusate pressure source incapable of providing pressures greater than 100 mm Hg.
8. The method of claim 1, wherein the organ is perfused at the first temperature with the first medical fluid utilizing a pneumatically pressurized medical fluid reservoir controlled in response to a pressure sensor disposed in tubing inserted
30 into the organ.
9. The method of claim 9, further comprising utilizing a stepping motor-activated cam valve controlled in response to the pressure sensor disposed in tubing

inserted into the organ to at least one of reduce perfusion pressure and impose a pulse wave on the medical fluid.

10. The method of claim 9, wherein a stepping motor-cam valve is provided for each organ.

5 11. The method of claim 1, further comprising collecting medical fluid that has passed through the organ in a separate organ bath for each organ, removing medical fluid from each organ bath, filtering the medical fluid and returning the medical fluid to each organ bath.

10 12. The method of claim 1, further comprising collecting medical fluid that has passed through the organ from each organ bath and sensing characteristics of the collected medical fluid indicative of organ viability to allow a determination of whether the viability of the organ has been at least one of sustained and restored.

15 13. The method of claim 1, further comprising collecting medical fluid that has passed through the organ in each organ bath, filtering, degassing and oxygenating the medical fluid and then either returning the medical fluid to each organ bath or to a medical fluid reservoir based on a sensed pH level of the medical fluid.

14. The method of claim 1, wherein the method further comprises submerging the organ in a second medical fluid at a second temperature to at least one of store and transport the organ.

20 15. The method of claim 1, wherein the method further comprises perfusing the organ with a second medical fluid at a second temperature at least one of intermittently and continuously to at least one of store and transport the organ.

25 16. The method of claims 14 or 15, wherein the second fluid contains substantially no oxygen.

17. The method of claim 16, wherein the second fluid is a simple crystalloid solution.

18. The method of claim 17, wherein the second fluid contains antioxidants.

30 19. The method of claims 14 or 15, wherein the second temperature is at most 15°C.

20. The method of claim 15, further comprising monitoring the viability of the organ during perfusion at the second temperature.

21. The method of claims 5 or 20, wherein the viability of each organ is monitored by a sensor that senses fluid characteristics indicative of organ viability and at least one of displays sensed data and relays sensed data to a microprocessor for assessment.

5 22. The method of claim 15, wherein the organ is perfused at the second temperature at a pressure within a range of approximately 5 to 40 mm Hg.

23. The method of claim 15, wherein the organ is perfused at the second temperature utilizing a pressurized medical fluid reservoir configured to provide pressure no greater than 40 mm Hg.

10 24. The method of claim 15, wherein the organ is perfused with the second medical fluid at the second temperature utilizing gravity from a pressure head medical fluid reservoir.

25. The method of claim 24, further comprising utilizing a stepping motor-activated cam valve provided for each organ and controlled in response to the pressure sensor disposed in tubing inserted into each organ to at least one of reduce perfusion pressure and put a pulse wave on the medical fluid.

26. The method of claims 14 or 15, further comprising transplanting the organ into a mammal while the organ remains at the second temperature.

20 27. The method of claim 26, further comprising again perfusing the organ with the first medical fluid at the first temperature after the organ has been transplanted into a mammal.

28. The method of claim 26, further comprising again perfusing the organ with the first medical fluid at the first temperature prior to transplanting the organ into a mammal.

25 29. The method of claim 28, further comprising again perfusing the organ with the second fluid at the second temperature prior to transplanting the organ into a mammal.

30. The method of claim 1, further comprising prior to perfusing the at least one organ with the first medical fluid at the first temperature, perfusing the organ with a medical fluid containing little or no oxygen.

30 31. The method of claim 30, wherein the medical fluid containing little or no oxygen includes antioxidants.

32. The method of claim 30, wherein the organ is perfused with the medical fluid containing little or no oxygen at a temperature of at least 15°C.

33. The method of claim 30, wherein the portable housing is capable of maintaining the organ at a temperature of at most 15°C.

5 34. The method of claim 1, further comprising monitoring the position of the organ using a global positioning system.

35. A method of at least one of maintaining and restoring the viability of at least one organ subjected to a period of ischemia, comprising:
perfusing said at least one organ with a first medical fluid at a first
10 temperature to at least one of maintain and restore pre-ischemia energy levels in the organ; and

perfusing the organ with a second medical fluid at a second temperature to at least one of store and transport the organ.

36. The method of claim 35, wherein the first medical fluid is an oxygenated solution and the second fluid contains substantially no oxygen.
15

37. The method of claim 36, wherein the first medical fluid is an oxygenated hemoglobin-based solution and the second fluid is a simple crystalloid solution augmented with antioxidants.

38. The method of claim 35, wherein the first temperature is at least about 15°C and the second temperature is at most 15°C.
20

39. The method of claim 35, further comprising monitoring the viability of the organ during perfusion of the organ with the first medical fluid at the first temperature and during perfusion of the organ with the second medical fluid at the second temperature.

25 40. A method of perfusing an organ, comprising:

perfusing an organ utilizing at least one medical fluid reservoir, a fluid pathway connected to the reservoir and connectable to the organ, and a perfusion pressure controller that controls pressure of the perfusate from the medical fluid reservoir.

30 41. The method of claim 40, wherein the at least one medical fluid reservoir is in communication with a pressure source and the fluid pathway, wherein the reservoir and pathway are configured to perfuse the organ at a perfusion pressure controlled at least in part by varying the pressure provided to the reservoir by the

pressure source, wherein the reservoir is a flexible container and the pressure source comprises a cuff disposed around the container.

42. The method of claim 41, wherein the pressure source is incapable of providing a pressure exceeding 100 mm Hg.

5 43. The method of claim 40, wherein the pressure controller includes a stepper motor-activated cam valve disposed on the fluid pathway, wherein the perfusion pressure is controlled at least in part by the stepper motor-activated cam valve.

10 44. The method of claim 40, wherein the pressure controller includes a gravity pressure head tank in communication with the at least one medical fluid reservoir, with the fluid pathway connected to the pressure head tank, wherein the pressure head tank and pathway are configured to perfuse the organ at a perfusion pressure controlled at least in part by the gravity pressure head.

15 45. A method of transporting and storing an organ, comprising, in sequence:

- a. perfusing said organ at a normothermic temperature to repair damage from warm ischemia;
- b. perfusing said organ at a hypothermic temperature;
- c. at least one of transporting and storing said organ at a
20 hypothermic temperature; and
- d. perfusing said organ at a normothermic temperature to repair damage from the hypothermic transport or storage of step c.

25 46. The method of claim 45, wherein said normothermic perfusing steps a and d are performed with an oxygenated perfusion fluid and said hypothermic perfusing step b is performed with a non-oxygenated perfusion fluid.

47. The method of claim 45, wherein step c comprises transporting said organ, and said method further comprises:

- e. perfusing said organ at a hypothermic temperature after step d.

30 48. The method of claim 47, further comprising:

- f. storing said organ at a hypothermic temperature after step e.

49. The method of claim 47, further comprising transplanting said organ after step e.

50. The method of claim 45, wherein step c comprises transporting said organ to a storage facility, and said method further comprises:

e. perfusing said organ at a hypothermic temperature and storing said organ at a hypothermic temperature at said storage facility after step d.

5 51. The method of claim 50, further comprising:

f. perfusing said organ at a normothermic temperature to repair damage from the hypothermic storage of step e;

g. perfusing said organ at a hypothermic temperature; and

10 h. transporting said organ to a transplant facility at a hypothermic temperature.

52. The method of claim 51, further comprising transplanting said organ after step h.

53. The method of claim 51, further comprising:

15 f. perfusing said organ at a normothermic temperature to repair damage from the hypothermic transport of step h;

g. perfusing said organ at a hypothermic temperature; and

h. transplanting said organ.

54. Apparatus for perfusing at least one organ, comprising:

at least one flexible medical fluid reservoir;

20 a pressure controller in communication with the at least one flexible medical fluid reservoir; and

a fluid pathway connected to the reservoir and connectable to the organ, wherein the organ perfusion pressure is controlled at least in part by varying the pressure with the pressure controller.

25 55. The apparatus of claim 54, wherein the pressure controller is a pressure cuff disposed around the at least one flexible medical fluid reservoir.

56. The apparatus of claim 55, wherein the pressure of the pressure cuff is provided by a tank containing compressed gas.

30 57. The apparatus of claim 55, wherein the pressure of the pressure cuff is provided by a compressor.

58. The apparatus of claim 54, further comprising a global positioning system for monitoring the location of the organ.

59. The apparatus of claim 54, wherein the pressure controller includes a stepper motor-activated cam valve disposed on the fluid pathway, wherein the organ perfusion pressure is controlled at least in part by the stepper motor-activated cam valve.

5 60. The apparatus of claim 54, wherein the pressure controller includes a gravity pressure head tank in fluid communication with the at least one medical fluid reservoir, wherein the fluid pathway is connected to the pressure head tank and the organ perfusion pressure is controlled at least in part by the gravity pressure head.

61. The apparatus of claims 55, 59 or 60, further comprising:
10 a pressure sensor disposed in a tip of the fluid pathway connectable to the organ, wherein the pressure controller is controlled in response to signals from the pressure sensor.

62. Apparatus for perfusing at least one organ, comprising:
at least one medical fluid reservoir;
15 a fluid pathway connected to the reservoir and connectable to the organ;
a first heat exchanger in heat exchange communication with the medical fluid reservoir; and
a controller for controlling the first heat exchanger to allow perfusion of the organ with medical fluid at both normothermic and hypothermic temperatures.

20 63. The apparatus of claim 62, further comprising;
an organ chamber for holding an organ to be perfused and an organ bath of medical fluid that has passed through the organ; and
a second heat exchanger in heat exchange communication with the organ chamber, wherein the controller controls the second heat exchanger to maintain
25 the organ bath selectively at both normothermic and hypothermic temperatures.

64. The apparatus of claim 62, wherein the controller is a microprocessor.

65. Apparatus for holding an organ for at least one of perfusion, storage and transport of the organ, comprising:
a portable housing;
30 an organ supporting surface configured to support an organ while allowing effluent medical fluid to pass therethrough, wherein the portable housing is configured to be received by an organ perfusion device and includes openings configured to allow tubing to pass therethrough and be connected to the organ.

66. The apparatus of claim 65, further comprising:
tubing connectable to the organ to allow perfusion of the organ; and
at least one connection device configured to allow connection of the tubing to
tubing of an organ perfusion device.
- 5 67. The apparatus of claims 65 or 66, further comprising a valve supported
on an upper portion of the housing and configured to control the pressure of medical
fluid passed through tubing operably connected to said valve.
68. The apparatus of claim 67, wherein the valve is a stepper motor-
activated cam valve.
- 10 69. The apparatus of claim 65, wherein a bottom portion of the housing is
liquid-tight and configured to collect medical fluid that has passed through a perfused
organ to form an organ bath.
70. The apparatus of claim 65, further comprising a handle disposed on an
outer surface of the portable housing.
- 15 71. The apparatus of claim 65, further comprising supports configured to
support the apparatus when inserted into an organ perfusion device.
72. A perfusion solution kit, comprising a saleable package containing at
least one first container holding a first perfusion solution for normothermic perfusion
and at least one second container holding a second, different perfusion solution for
20 hypothermic perfusion.
73. The kit of claim 72, wherein said first perfusion solution contains at
least one oxygen carrier.
74. The kit of claim 73, wherein said first perfusion solution is oxygenated
and said second perfusion solution is non-oxygenated.
- 25 75. The kit of claim 73, wherein said oxygen carrier is selected from the
group consisting of a hemoglobin and stabilized red blood cells.
76. The kit of claim 73, wherein said oxygen carrier is a hemoglobin.
77. The kit of claim 73, wherein said second perfusion solution contains at
least one anti-oxidant.
- 30 78. The kit of claim 72, wherein said second solution contains no more
than 5 mM of dissolved pyruvate salt.
79. The kit of claim 73, wherein said second perfusion solution contains at
least one vasodilator.

80. The kit of claim 72, wherein said first container and said second container are configured to be operably connected to a perfusion machine as perfusion fluid reservoirs in fluid communication with perfusate conduits of said perfusion machine.

5 81. The kit of claim 80, wherein at least one of said first container and said second container is compressible to apply pressure to the perfusion solution therein.

82. The kit of claim 80, wherein at least one of said first container and said second container includes a first opening for passage of a contained perfusion solution out of said container and a second opening passage of a compressed gas into said
10 container.

83. The kit of claim 80, wherein said package is a cassette configured to be operably connected to a perfusion machine for connection of said first container and said second container within said cassette in fluid communication with perfusate conduits of said perfusion machine.

15 84. A control system for controlling perfusion to at least one organ with a medical fluid to maintain viability of the at least one organ, comprising:

an input for inputting organ data;

a perfusion selector for selecting one or more types of perfusion
modes;

20 a flow control selector for selecting a type of flow control for each selected perfusion mode;

a controller for controlling flow of the medical fluid based on the selected perfusion mode and flow control;

25 at least one detector for detecting operating conditions experienced by the medical fluid and organ during perfusion;

a comparator for comparing detected operating conditions with prestored operating conditions and generating a signal indicative of organ viability based on the comparison; and

30 an indicator for generating a message relating to organ viability based on the signal generated by the comparator.

85. The control system of claim 84, wherein the flow control selector permits selection between aerobic and anaerobic perfusion for each selected perfusion mode.

86. The control system of claim 84, wherein the perfusion selector selects at least one of hypothermic perfusion, normothermic perfusion, and sequential normothermic and hypothermic perfusion.

5 87. The control system of claim 84, wherein the perfusion selector selects a plurality of medical fluids at different temperatures.

88. The control system of claim 84, wherein the perfusion selector selects at least one of intermittent perfusion, single pass perfusion, and recirculation perfusion.

10 89. The control system of claim 84, wherein the flow control selector selects flow control based on at least one of perfusate flow rate, perfusate pH, organ inlet pressure and timed sequences.

90. The control system of claim 84, wherein the at least one detector includes a pressure sensor, a pH detector, and an oxygen sensor.

15 91. The control system of claim 84, further comprising a thermal controller for controlling temperature of at least one of the perfusate and the organ.

92. The control system of claim 91, further comprising an organ container and a perfusate reservoir, wherein the thermal controller regulates temperature of at least one of the organ container and the perfusate reservoir.

20 93. The control system of claim 91, further comprising a temperature sensor that outputs temperature readings to the thermal controller.

94. The control system of claim 84, wherein the perfusion selector and flow control selector include default settings based on organ type.

95. The control system of claim 84, wherein the controller controls perfusion to a plurality of organs.

25 96. The control system of claim 84, wherein the input accepts data relating to organ type and organ mass.

97. A method of controlling perfusion of at least one organ with medical fluid, comprising:

30 inputting organ data;
 selecting one or more types of perfusion modes;
 selecting a type of flow control for each selected perfusion mode;
 controlling flow of the medical fluid based on the selected perfusion mode and flow control;

detecting operating conditions experienced by the medical fluid and organ during perfusion;

comparing detected operating conditions with prestored operating conditions and generating a signal indicative of organ viability based on the comparison; and

generating a message relating to organ viability based on the signal generated by the comparator.

98. The method of claim 97, wherein selecting a type of flow control includes selecting between aerobic and anaerobic perfusion for each selected perfusion mode.

99. The method of claim 97, wherein selecting one or more types of perfusion modes includes selecting at least one of hypothermic perfusion, normothermic perfusion, and sequential normothermic and hypothermic perfusion.

100. The method of claim 97, wherein selecting one or more types of perfusion modes includes selecting a plurality of medical fluids at different temperatures.

101. The method of claim 97, wherein selecting one or more types of perfusion modes includes selecting at least one of intermittent perfusion, single pass perfusion, and recirculation perfusion.

102. The method of claim 97, wherein selecting a type of flow control includes selecting flow control based on at least one of perfusate flow rate, perfusate pH, organ inlet pressure and timed sequences.

103. The method of claim 97, wherein detecting operating conditions includes detecting pressure, pH, and oxygen levels.

104. The method of claim 97, further comprising controlling temperature of at least one of the perfusate and the organ with a thermal controller.

105. The method of claim 104, wherein controlling the temperature includes regulating temperature of at least one of the organ container and a perfusate reservoir.

106. The method of claim 104, further sensing a temperature of at least one of an organ, an organ container, and a perfusate reservoir and outputting temperature readings to the thermal controller.

107. The method of claim 97, further comprising setting default settings based on organ type for use in the steps of selecting perfusion mode and flow control.

108. The method of claim 97, including controlling perfusion to a plurality of organs.

109. The method of claim 97, wherein inputting organ data includes inputting data relating to organ type and organ mass.

5 110. A recording medium that stores a control program for use by perfusion system that perfuses at least one organ with a medical fluid, the control program including instructions for:

inputting organ data;

selecting one or more types of perfusion modes;

10 selecting a type of flow control for each selected perfusion mode;

controlling flow of the medical fluid based on the selected perfusion mode and flow control;

detecting operating conditions experienced by the medical fluid and organ during perfusion;

15 comparing detected operating conditions with prestored operating conditions and generating a signal indicative of organ viability based on the comparison; and

generating a message relating to organ viability based on the signal generated by the comparator.

20 111. The recording medium of claim 110, wherein selecting a type of flow control includes selecting between aerobic and anaerobic perfusion for each selected perfusion mode.

25 112. The recording medium of claim 110, wherein selecting one or more types of perfusion modes includes selecting at least one of hypothermic perfusion, normothermic perfusion, and sequential normothermic and hypothermic perfusion.

113. The recording medium of claim 110, wherein selecting one or more types of perfusion modes includes selecting a plurality of medical fluids at different temperatures.

30 114. The recording medium of claim 110, wherein selecting one or more types of perfusion modes includes selecting at least one of intermittent perfusion, single pass perfusion, and recirculation perfusion.

115. The recording medium of claim 110, wherein selecting a type of flow control includes selecting flow control based on at least one of perfusate flow rate, perfusate pH, organ inlet pressure and timed sequences.

5 116. The recording medium of claim 110, wherein detecting operating conditions includes detecting pressure, pH, and oxygen levels.

117. The recording medium of claim 110, further comprising controlling temperature of at least one of the perfusate and the organ with a thermal controller.

10 118. The recording medium of claim 117, wherein controlling the temperature includes regulating temperature of at least one of the organ container and a perfusate reservoir.

119. The recording medium of claim 117, further sensing a temperature of at least one of an organ, an organ container, and a perfusate reservoir and outputting temperature readings to the thermal controller.

15 120. The recording medium of claim 110, further comprising setting default settings based on organ type for use in the steps of selecting perfusion mode and flow control.

121. The recording medium of claim 110, including controlling perfusion to a plurality of organs.

20 122. The recording medium of claim 110, wherein inputting organ data includes inputting data relating to organ type and organ mass.

1/12




FIG. 1




FIG. 2









FIG.3






FIG. 9




FIG.10

7/12




FIG. 11A




FIG. 11B




FIG. 11D




FIG. 11C

9/12




FIG. 12




FIG. 13A




FIG. 13B

11/12

FIG.14A




FIG.14B




FIG.14C




FIG.14D




FIG.14E





FIG.14F



12/12




FIG. 15

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : A01N 1/02	A3	(11) International Publication Number: WO 00/18226 (43) International Publication Date: 6 April 2000 (06.04.00)
(21) International Application Number: PCT/US99/22582 (22) International Filing Date: 29 September 1999 (29.09.99) (30) Priority Data: 09/162,128 29 September 1998 (29.09.98) US (71) Applicant: LIFE SCIENCE HOLDINGS, INC. [US/US]; 1510 West Montana Street, Chicago, IL 60614-2013 (US). (72) Inventors: OWEN, Donald, R.; Vital Assist, Inc., Suite I, 5701 Crawford Street, Harahan, LA 70123 (US). KRAVITZ, David, C.; Life Science Holdings, Inc., Suite 500, 1510 West Montana Street, Chicago, IL 60614-2013 (US). (74) Agents: OLIFF, James, A. et al.; Oliff & Berridge, plc, P.O. Box 19928, Alexandria, VA 22320 (US).	(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> (88) Date of publication of the international search report: 25 May 2000 (25.05.00)	
(54) Title: APPARATUS AND METHOD FOR MAINTAINING AND/OR RESTORING VIABILITY OF ORGANS		
(57) Abstract <p>An organ perfusion apparatus and method for monitoring, sustaining and/or restoring the viability of the organ and for preserving the organ for storage and/or transport perfuse the organ at normothermic temperatures (normothermic perfusion mode), preferably prior to and followed by organ perfusion at hypothermic temperatures (hypothermic perfusion mode) for transport and/or storage of the organ. The restoring of organ viability is accomplished by restoring high energy nucleotide (e.g., ATP) levels in the organ, which were reduced by warm ischemia time, by perfusing the organ with a medical fluid, such as an oxygenated cross-linked hemoglobin-based bicarbonate medical fluid, at normothermic temperatures. In the normothermic perfusion mode, organ perfusion pressure is preferably controlled in response to a sensor disposed in an end of tubing placed in the organ, by a pneumatically pressurized medical fluid reservoir which may be used in combination with a stepping motor/cam valve which provides for perfusion pressure fine tuning, preventing overpressurization and providing emergency flow cut-off. In the hypothermic mode, the organ is perfused with a medical fluid, preferably a simple crystalloid solution augmented with antioxidants, intermittently or at a slow continuous flow rate. The medical fluid may be fed into the organ by gravity from an intermediary tank which has a low pressure head so overpressurization of the organ is avoided. In either mode, preventing overpressurization prevents and/or reduces damage to the vascular endothelial lining and to the organ tissue in general. Also, viability of the organ may be automatically monitored in either mode, preferably by monitoring fluid characteristics of the medical fluid that has been perfused through the organ, such fluid characteristics being indicative of organ viability. The perfusion process can be automatically controlled using a control program.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 99/22582

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A01N1/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 43899 A (BREONICS INC) 27 November 1997 (1997-11-27) see: page 14, line 5 - 28; page 18, line 16 - 36; example 8.	1-39
X	WO 97 45527 A (TRANS D A T A SERVICE INC ; HEACOX JOHN K (US); GARDETTO WILLIAM W) 4 December 1997 (1997-12-04) see: page 2, line 1 - 7; page 2, line 24 - page 3, line 4; page 8, line 22 - 26. - -/-	1-39, 65-71

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *A* document member of the same patent family

Date of the actual completion of the international search

21 March 2000

Date of mailing of the international search report

31 03. 00

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Klaver, J

INTERNATIONAL SEARCH REPORT

Int lional Application No
PCT/US 99/22582

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 96 29865 A (ORGAN INC ;LIFE RESUSCITATION TECH (US); AMERICAN NAT RED CROSS (U) 3 October 1996 (1996-10-03) see: page 5, line 25 - 37; page 8, line 15 - 24; page 11, line 33 - 35; page 27, line 4 - 14.	1-39, 65-71
X	page 7, line 20-26; page 25, line 1 - 17.	40-44, 54-61
X	WO 94 06292 A (PERFUSION MEDICAL LAB INC) 31 March 1994 (1994-03-31) see: page 8, line 20 - 30; page 9, line 26 - 36; page 13, line 17 - page 14, line 9; page 16, line 5 - 21; page 17, line 4 - 17.	1-39, 65-71
X	page 10, line 28 -page 11, line 29	40-44, 54-61
X	WO 91 09520 A (UNIV CALIFORNIA) 11 July 1991 (1991-07-11) cited in the application see: page 8, line 34/35; page 17, line 6 - 13; example 2.	1-39
X	EP 0 376 763 A (MCKELVEY KAREN ;MACKEY JOHN (US); OLSON MYRON (US); HOLLOWAY RAY H) 4 July 1990 (1990-07-04) see: col. 3, par. 1; col. 3, line 47 - col. 4, line 3; col. 4, line 9 - 19; col. 4, line 31 - 39; col. 6, line 23 - 58.	65-71
X	column 10, line 4-19	40-44, 54-61
X	WO 88 05261 A (TOPS SYSTEMS INC) 28 July 1988 (1988-07-28) see: page 3, line 29 - 36; page 4, line 14 - 28; page 9, line 28 - 36; page 12, 1st par.; page 13, line 34 - page 14, line 9; page 18, line 5 - 19; page 23, line 33 - page 24, line 2; Example 3.	1-39, 65-71
X	see page 14, par. 1; page 15, par. 5.	40-44, 54-61
X	US 3 881 990 A (BURTON THOMAS A ET AL) 6 May 1975 (1975-05-06) the whole document	65-71
X	US 5 051 352 A (MARTINDALE JAMES G ET AL) 24 September 1991 (1991-09-24) see: col. 5, line 15-col. 6, line 35; col. 7, line 1 - 32.	40-44, 62-64, 84-122
	--- -/--	

INTERNATIONAL SEARCH REPORT

Int lional Application No
PCT/US 99/22582

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 326 706 A (YLAND MARC J ET AL) 5 July 1994 (1994-07-05) see: col. 1, line 60-65; col. 2, line 50 - 58; col. 3, line 18 - 32; col. 17, line 16 - 33; figures; table in col. 9/10.	40-44, 54-61, 84-122
X	WO 91 14364 A (WATERS INSTR INC) 3 October 1991 (1991-10-03) see: page 13, 3rd full par.; page 16, line 9 - 26; page 21, 3rd par.	40-44, 53-61
X	US 5 141 847 A (SUGIMACHI KEIZO ET AL) 25 August 1992 (1992-08-25) cited in the application column 4, line 3-19	40,44, 54,60
X	FR 2 592 306 A (COUEGNAS JACQUES) 3 July 1987 (1987-07-03) the whole document	54-57
P,X	WO 99 15011 A (HASSANEIN WALEED H) 1 April 1999 (1999-04-01) see: page 12, line 1 - page 13, line 8; page 14, line 11 - 27; page 20, line 23 - page 21, line 29; page 22, line 5 - 26; page 49, line 8 - 15.	40,54, 60-64, 72-83
X	US 5 699 793 A (BRASILE LAUREN) 23 December 1997 (1997-12-23) the whole document	40, 84-109
X	WO 97 46091 A (MEDTRONIC INC) 11 December 1997 (1997-12-11) see: page 2, line 20/21; page 4, line 14 - 21; page 6, line 29 - page 7, line 14.	40,45, 54, 62-64, 84-109
X	US 4 473 637 A (GUIBERT RAUL) 25 September 1984 (1984-09-25) column 3, line 19-62; figure 1	45-53, 62-64
X	WO 86 00812 A (PHARMACIA AB) 13 February 1986 (1986-02-13) see: page 6, line 10 - 12; page 8, line 12 - 22; page 10, line 15 - 17.	72-83
X	US 4 231 354 A (KURTZ ROBERT J ET AL) 4 November 1980 (1980-11-04) see: col. 2, line 18 - 35; col. 3, line 1 -19; col. 3, line 49 - col. 4, line 15.	84-122

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US 99/22582

Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this International application, as follows:

see additional sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1 - 39, 65 - 71

Method of maintaining or restoring viability of an organ comprising: a) perfusing the organ with an oxygenated medical fluid, preferably at a temperature of $> 15^{\circ}\text{C}$, optionally and preferably followed by a perfusion at a lower temperature with a second medical fluid.
b) storing and transporting the organ in an organ cassette including a portable housing, supporting surface and tubing.

Apparatus for use in the method of claims 1 - 39

2. Claims: 40 - 44, 54 - 61

Method for perfusing an organ utilizing at least one medical fluid reservoir and a perfusion pressure controller.
Apparatus for use in this method.

3. Claims: 45 - 53

Method for transporting and storing an organ comprising
a. perfusing at normothermic temperature, preferably with oxygenated fluid
b. perfusing at hypothermic temperature, preferably with non-oxygenated fluid
c. transporting and storing organ at hypothermic temperature
d. perfusing at normothermic temperature to repair damage of step c.

4. Claims: 62 - 64

Apparatus for perfusing an organ comprising reservoir, pathway, one or more heat exchangers and control device for regulating heat exchanger(s), preferably a microprocessor.

5. Claims: 72 - 83

Perfusion solution kit comprising a sealable package containing a first container holding a first (preferably oxygenated) perfusion solution and a second container holding a different perfusion solution.

6. Claims: 84 - 109

Control system for controlling perfusion of an organ comprising: input, perfusion mode selector, flow control

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

selector and -controller, detector, comparator and indicator.
Method of controlling perfusion of an organ by using this
system.

7. Claims: 110 - 122

Recording medium for storing control program for use in
perfusion system.

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int: Jondl Application No

PCT/US 99/22582

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9743899 A	27-11-1997	US 5843024 A AU 3067197 A CA 2255657 A CN 1226132 A	01-12-1998 09-12-1997 27-11-1997 18-08-1999
WO 9745527 A	04-12-1997	US 5965433 A CA 2228422 A EP 0842261 A	12-10-1999 04-12-1997 20-05-1998
WO 9629865 A	03-10-1996	AU 5375496 A	16-10-1996
WO 9406292 A	31-03-1994	US 5338662 A AU 5131093 A CA 2144952 A EP 0665713 A US 5494822 A	16-08-1994 12-04-1994 31-03-1994 09-08-1995 27-02-1996
WO 9109520 A	11-07-1991	US 5066578 A US 5075210 A AU 7175591 A	19-11-1991 24-12-1991 24-07-1991
EP 0376763 A	04-07-1990	AU 633280 B AU 4382789 A CA 2001553 A JP 4099701 A	28-01-1993 03-05-1990 26-04-1990 31-03-1992
WO 8805261 A	28-07-1988	NONE	
US 3881990 A	06-05-1975	US 3777507 A	11-12-1973
US 5051352 A	24-09-1991	NONE	
US 5326706 A	05-07-1994	NONE	
WO 9114364 A	03-10-1991	NONE	
US 5141847 A	25-08-1992	JP 1930030 C JP 3075063 A JP 6053160 B	12-05-1995 29-03-1991 20-07-1994
FR 2592306 A	03-07-1987	NONE	
WO 9915011 A	01-04-1999	AU 9504298 A	12-04-1999
US 5699793 A	23-12-1997	US 6024698 A AU 2517395 A AU 2595195 A EP 0759692 A WO 9531944 A WO 9531897 A	15-02-2000 18-12-1995 18-12-1995 05-03-1997 30-11-1995 30-11-1995
WO 9746091 A	11-12-1997	US 5716378 A AU 3142897 A	10-02-1998 05-01-1998
US 4473637 A	25-09-1984	NONE	
WO 8600812 A	13-02-1986	AU 4671385 A CA 1246449 A	25-02-1986 13-12-1988

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int: Jonal Application No

PCT/US 99/22582

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 8600812 A		EP 0188595 A	30-07-1986
		JP 61502821 T	04-12-1986
US 4231354 A	04-11-1980	AU 522816 B	24-06-1982
		AU 4889179 A	17-01-1980
		DE 2928223 A	24-01-1980
		FR 2430771 A	08-02-1980
		GB 2025662 A, B	23-01-1980
		IT 1117406 B	17-02-1986
		JP 55014096 A	31-01-1980